Product datasheet

Specifications



Symmetra PX 96kW Scalable to 160kW, without Bypass, Distribution, or Batteries, 400V

SY96K160H-NB

Overview

Presentation	A high-efficiency, modular 3-phase UPS that offers internal redundancy for your data center requirements. With scalable power, this UPS grows with your data center up to 160kW/kVA. Pair with the Classic Battery Cabinet and the Wall-Mount or 300mm Maintenance Bypass Panel to complete your power protection solution. Please click here for Classic Battery Cabinet runtime information. Suitable for small to medium data centers or individual zones of large data centers.

Main

Main input voltage	400 V AC 3 phases 380 V AC 3 phases 415 V AC 3 phases
Maximum input current	197 A
Max short time withstand current	30 kA
Input harmonic distortion	Less than 5 % for full load
Load power factor	0.5 leading to 0.5 lagging
Cos phi	0.99
Switching current capacity	315 A
Efficiency at full load	340...477 V
Input connection	1 hard wire 5-wire (3P + N + E)
Input frequency	40...70 Hz
Output voltage	400 V AC 3 phases 380 V AC 3 phases 415 V AC 3 phases
Rated power in W	96000 W
Rated power in VA	96000 VA
Output connection	Hard wire 5-wire (3P + N + E) for 1 zone(s)
Bypass type	Built-in static bypass
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	160000 VA
Maximum configurable power in W	160000 W
Output harmonic distortion	< 2% for 0 to 100% linear load and < 5% for full non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Output voltage tolerance	+/- 1% static and +/- 5% at 100% load step
UPS topology	Double conversion online
Waveform type	Sine wave

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Efficiency	95 % (full load) 95 % (half load) 94 % (in battery operation)
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Neutral output current	240 A
Required output current protection	250 A
Replacement battery	SYPBV96K160HA SYPBV96K160HB

Graphs

Run Time	View Runtime Graph

Complementary

Additional information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
Battery type	Lead-acid external
Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slot	2
Preinstalled device	Network management card with CAN
UPS connectivity	Pre-installed network management card 3
Color	Black
Height	199.1 cm
Width	60 cm
Depth	107 cm
Product weight	496 kg
USB compatible	No
Provided equipment	Network management card Start-up service User manual
Bypass wiring configuration	5 wire (3P + N + E)
Max bypass input current	250 A
Bypass current protection	250 A
Number of power module filled slots	6
Number of power module free slots	4
Redundant	Yes

Environment

Standard	EN 50091-1 EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3 ISO 14001 ISO 9001 VFI-SS-111
Ambient air temperature for operation	0…40 °C

Ambient air temperature for storage	-15…40 °C
Storage altitude	0…15240 m
IP protection	IP20
Relative humidity	0…95 %
Storage relative humidity	0…95 %
NEMA degree of protection	NEMA 1
Acoustic level	63 dBA
Heat dissipation	17244 Btu/h
Operating altitude	0...3333 ft

Batteries & Runtime

Battery type	External battery system
Extendable runtime	0
Empty battery slot	0

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	214 cm
Package 1 Width	121 cm
Package 1 Length	84.8 cm
Package 1 Weight	547 kg

Contractual warranty

Warranty (in months)	12

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

SCIP Number	F4c2965e-f80d-4830-8cd4-be926afb0f45
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again

Repack and remanufacture

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins