Product datasheet

Specifications



APC Smart-UPS RT 2200VA 230V - Marine

SURTD2200XLIM

Overview

Presentation	High availability, ruggedized power protection for shipboard and other transportation applications.

Main

Main input voltage	230 V
Other input voltage	220 V 240 V
Input connection	BS 1363 British IEC 60320 C20 CEE 7/7
Efficiency at full load	180...280 V
Input frequency	50/60 Hz +/- 5 Hz auto-sensing
Output voltage	230 V
Other output voltage	220 V 240 V
Rated power in W	1540 W
Rated power in VA	2200 VA
Output connection	8 IEC 60320 2 IEC Jumpers 2 IEC 60320
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	Less than 3 %
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1540 W
UPS topology	On-Line
Waveform type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Replacement battery	APCRBC140

Graphs

Run Time	View Runtime Graph

Complementary

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Emergency power off	Yes
Free slot	0
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge energy rating	555 J
Noise filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Number of rack unit	3U
Cable length	2.5 m
Number of cables	1
Color	Black
Height	432 mm
Width	130 mm
Depth	660 mm
Product weight	54.55 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	No
Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Smart UPS signalling RS-232 cable User manual
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	CE DNV KCC
Standard	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0…55 °C
Ambient air temperature for storage	-15…45 °C
Storage altitude	0…15240 m
IP protection	IP20
Relative humidity	0…95 % non-condensing
Storage relative humidity	0…95 % non-condensing
Acoustic level	55 dBA

Heat dissipation	609 Btu/h
Operating altitude	0...10000 ft

Batteries & Runtime

Battery type	Lead-acid battery
Extendable runtime	1
Included battery module	2
Typical recharge time	2.5 h
RBC quantity	1
Battery life	3…5 year(s)
Battery charging power	382 W rated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.7 cm
Package 1 Width	60.3 cm
Package 1 Length	98 cm
Package 1 Weight	63.64 kg

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**4 342 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**1 356 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**16 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**2 960 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**4 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**4282bd22-a353-4f82-bb5c-97bbd7f1d1e9**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Recyclability potential, in %	**58**
End of life manual availability	**End of Life Information**
Removable battery	**User replaceable**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative



