Product datasheet

Specifications



Easy UPS 1 Ph On-Line, 10kVA/ 10kW, Rackmount 4U, 230V, 1x Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, W/ rail kit

SRVS10KRIRK

To be discontinued

To be discontinued on: 31 Oct 2026

To be end-of-service on: 30 Aug 2029

Overview

Presentation	For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.

Main

Main input voltage	230 V AC 1 phase
Other input voltage	220 V 240 V
Efficiency at full load	110...300 V half load 176...300 V full load
Input connection	1 hard wire 3-wire (1P + N + E)
Input frequency	40...70 Hz auto sensing
Output voltage	230 V AC 1 phase
Other output voltage	220 V 240 V
Rated power in W	10000 W
Rated power in VA	10000 VA
Output connection	Hard wire 3-wire (1P + N + E) for 1 zone(s)
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	1 %
Maximum configurable power in VA	10000 VA
Maximum configurable power in W	10000 W
UPS topology	On-Line
Waveform type	Sine wave
Efficiency	94 % (full load)
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Complementary

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery type	Lead-acid external included
Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slot	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	Serial port USB port Available expansion slot
Surge energy rating	600 J
Number of rack unit	4U
Color	Black (RAL 7010)
Height	173 mm
Width	438 mm
Depth	710 mm
Product weight	69 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
USB compatible	Yes
Mounting position	Horizontal
Mounting mode	Rack-mounted with included kit
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Easy UPS 1Ph On-Line
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	CE UKCA
Standard	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0…40 °C
Ambient air temperature for storage	-15…60 °C
Storage altitude	0…15000 m
IP protection	IP20
Relative humidity	0…95 % non-condensing
Storage relative humidity	0…95 % non-condensing
Acoustic level	58 dBA

Heat dissipation	2128 Btu/h
Operating altitude	0...3000 m

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	192 V
Extendable runtime	0
Included battery module	0
Empty battery slot	0
Typical recharge time	5 h
Battery life	3…5 year(s)
Battery charging power	235 W rated
Battery power in VAh	1599 VAh runtime

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	48.500 cm
Package 1 Width	60.000 cm
Package 1 Length	83.600 cm
Package 1 Weight	79.000 kg

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**15 613 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**622 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**7 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**9 540 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**6 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**65871482-995d-4fb8-960b-f71cf07ec0ba**
EU RoHS Directive	**Compliant By Exemption**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**65**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative









Product datasheet SRVS10KRIRK

