Product datasheet

Specifications



Galaxy VS UPS 30kW 400V, 2 internal 9Ah smart modular battery strings, expandable to 4, Start-up 5x8

GVSUPS30KB4HS

Overview

Presentation	Highly efficient, easy-to-deploy 30kW, 400V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service and 2 smart high-capacity modular battery strings, expandable to 4 strings for extended runtime. Runtime charts available in the Documents tab.

Main

Main input voltage	400 V AC 3 phases 380 V AC 3 phases 415 V AC 3 phases
Other input voltage	380 V 415 V
Maximum input current	54 A
Max short time withstand current	65 kA
Input harmonic distortion	Less than 3 % for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating
Cos phi	0.99
Efficiency at full load	340...460 V 400 V
Input connection	1 hard wire 3-wire (3P + E) 1 hard wire 5-wire (3P + N + E)
Input frequency	40...70 Hz
Output voltage	400 V AC 3 phases 380 V AC 3 phases 415 V AC 3 phases
Rated power in W	30 kW
Rated power in VA	30 kVA
Output connection	Hard wire 5-wire (3P + N + E) for 1 zone(s)
Bypass type	Built-in static bypass
Crest factor	2.5
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	30 kVA
Maximum configurable power in W	30 kW
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Output voltage tolerance	+/-1% after 50ms
Waveform type	Sine wave

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Output frequency	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised

Complementary

Max current discharge	81 A
Battery type	Lead-acid internal
Control panel	Touch screen LCD user interface
Free slot	1
UPS connectivity	Embedded network management card 4
Color	White
Height	148.5 cm
Width	52.1 cm
Depth	84.7 cm
Product weight	460 kg
USB compatible	No
Provided equipment	Battery modules ship installed Dust filter EcoStruxure IT ready (UPS) Installation guide Integrated network management Power modules ship installed Start-up service
Bypass voltage tolerance	+/- 10 %
Redundant	No
Range of product	Galaxy VS
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	UL 1778 5th edition
Standard	CSA C22.2 No 107.3 EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 IEC 60721-4-2 level 2M2
Ambient air temperature for operation	0…40 °C
Ambient air temperature for storage	-15…40 °C
Storage altitude	0…3048 m
IP protection	IP20
Relative humidity	0…95 % non-condensing
Storage relative humidity	0…95 % non-condensing
Acoustic level	61 dBA
Heat dissipation	3395 Btu/h
Operating altitude	0...3281 ft

Batteries & Runtime

Battery type	Internal modular battery VRLA
Battery voltage	480 V
Extendable runtime	0
Discharge battery voltage	384 V DC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	168 cm
Package 1 Width	99 cm
Package 1 Length	64 cm
Package 1 Weight	490 kg

Contractual warranty

Warranty (in months)	12

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**37 004 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**5 382 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**227 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**53 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**30 196 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**1 146 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold

Energy efficiency

Energy Efficiency Optimized	**Energy efficient product**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**42**
End of life manual availability	End of Life Information
Removable battery	**Yes**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative









Product datasheet GVSUPS30KB4HS

